

M[✓]C™ UNDERSTANDING YOUR REPORT

ENGINES

TRANSMISSIONS

ALUMINUM:	PISTONS, BEARINGS, HOUSINGS, THRUST WASHERS, BUSHINGS	TORQUE CONVERTER, THE CASE, THRUST WASHERS, GEAR AND VANE PUMPS
CHROMIUM:	COMPRESSION RINGS, LOW FRICTION BEARINGS, LINERS, CHROMATE COOLING SYSTEM	BALL AND ROLLER BEARINGS
COPPER:	BEARINGS, BUSHINGS, THRUST WASHERS, OIL COOLER, CLUTCHES, AND AN OIL ADDITIVE IN SOME GASOLINE ENGINE OILS.	CLUTCH PLATES, BRONZE BUSHINGS, OIL COOLER OXIDES, BRASS FITTINGS
IRON:	CRANKSHAFT, CYLINDERS, PISTONS, LINERS, BEARINGS, VALVE TRAIN	GEARS, BEARINGS, SHAFTS, SOME CASES, CLUTCH PLATES
LEAD:	BEARINGS, CONTAMINATION FROM LEADED GASOLINE	GEARS
TIN:	PISTON SKIRTS, BEARINGS, AND BUSHINGS.	SOME BEARING CAGES
SILICON:	AIRBORN DIRT, SEAL MATERIAL, GASKETS, USED IN SOME OIL ADDITIVES, SPRAY LUBRICANTS, WHEN FOUND WITH POTASSIUM INDICATES GLYCOL ISSUE	AIRBORN DIRT, SEALERS, GASKETS, USED IN SOME OIL ADDITIVES, SPRAY LUBRICANTS, WHEN FOUND WITH POTASSIUM INDICATES GLYCOL ISSUE, SAND-CASTED PARTS
POTASSIUM:	INDICATION OF GLYCOL OR SALTWATER INTRUSION, ADDITIVE IN SOME OILS	INDICATION OF GLYCOL OR SALTWATER INTRUSION, ADDITIVE IN SOME OILS
SODIUM:	FOUND IN SOME OIL ADDITIVES, GLYCOL, ENVIRONMENTAL COMTAMINANT OR SALT WATER	FOUND IN SOME OIL ADDITIVES, GLYCOL, ENVIRONMENTAL COMTAMINANT OR SALT WATER
WATER:	MEASURED IN % VOLUME, CAN BE INDICATION OF CONDENSATION, COOLING SYSTEM LEAK, OR OUTSIDE CONTAMINATION	
GLYCOL:	MEASURED IN % VOLUME, IN THE FORMULATION OF MOST COMMERCIAL COOLANTS	
OXIDATION:	THIS IS THE RESULTS OF OXYGEN IN THE AIR REACTING WITH THE OIL AT ELEVATED TEMPERATURES. THIS IS A NORMAL PROCESS AS THE OIL AGES. IF AN ENGINE IS OPERATED CONTINUOUSLY AT A HIGH TEMPERATURE FOR EXTENDED PERIODS, OR IF DRAIN INTERVAL IS OVER EXTENDED, OIL CHANGE IS RECOMMENDED.	
NITRATION:	(GAS ENGINES ONLY) FORMED DURING COMBUSTION PROCESS, LEADS TO ACCELERATED OIL DETERIORATION.	
SOOT:	(DIESEL ENGINES ONLY) NORMAL COMBUSTION BY PRODUCT OF DIESEL FUEL AND APPEARS AS CONTAMINANT IN THE OIL CAUSING AN INCREASE IN VISCOSITY. INDICATE AN INPROPER AIR/FUEL RATIO, DEFECTIVE AIR INTAKE, FAULTY INJECTORS, OR BLOW-BY	
VISCOSITY:	CALCULATED MEASUREMENT OF THE OIL'S ABILITY TO FLOW AND LUBRICATE, INDICATES IF OIL IS TOO THICK OR THIN	
TBN:	MEASUREMENT OF OIL'S ALKALINE BASE RESERVE, ADDITIVE IN OIL CAPABLE OF NEUTRALIZING ACIDIC CONTAMINANTS, WHEN TBN IS BELOW 3, IT IS AN INDICATION THE OIL IS NO LONGER SERVICEABLE	
FUEL DILUTION:	MEASURED IN % VOLUME, CAN INDICATE FAULTY COMBUSTION, RICH AIR/FUEL MIXTURE WHEN PRESENT BETWEEN 2%-5%. INJECTOR PROPBLEM OR INTERNAL FUEL LINE LEAK IS TYPICALLY INDICATED WHEN FUEL IS DETECTED AT HIGH LEVELS	

ACCURACY OF RECOMMENDATIONS IS DEPENDENT ON THE REPRESENTATIVE OIL SAMPLES AND COMPLETELY CORRECT DATA ON BOTH UNIT AND OIL. THIS ANALYSIS IS INTENDED AS AN AID IN PREDICTING MECHANICAL WEAR. NO GUARANTEE, EXPRESS OR IMPLIED, IS MADE AGAINST FAILURE OF THIS COMPONENT, MOTOR CHECK(OIL LAB LLC.) LIABILITY IN ANY CASE IS LIMITED TO THE COST OF THE REPORTED ANALYSIS.